

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (currently amended): A transmission diversity detection circuit for notifying presence or absence of a transmission diversity of spread spectrum communication by modulation of SCH (Synchronization channel), comprising:

arithmetic means for calculating a calculated value of $C_{2n,0} \times S_{2n,0}^* + C_{2n,0}^* \times S_{2n,0} + C_{2n,1}^* \times C_{2n,1}$,

in first and second symbols in a predetermined number of series of slots with respect to a reception signal, taking a primary CPICH (common pilot channel) symbol with respect to said first symbol as $C_{2n,0}$, a SCH symbol with respect to said first symbol as $S_{2n,0}$, a primary CPICH symbol with respect to said second symbol as $C_{2n,1}$;

taking a complex conjugate of said primary CPICH symbol $C_{2n,0}$ as $C_{2n,0}^*$, a complex conjugate of SCH symbol $S_{2n,0}$ as $S_{2n,0}^*$, a complex conjugate of said primary CPICH symbol $C_{2n,1}$ as $C_{2n,1}^*$; and

judgment means for making judgment whether transmission diversity is present or not depending upon positive or negative of said calculated value.

2. (currently amended): A transmission diversity detection circuit as set forth in claim 1, wherein said arithmetic means comprises:

circuits for deriving said complex conjugate $C_{2n,0}^*$ of said primary CPICH symbol $C_{2n,0}$, a complex conjugate $S_{2n,0}^* \underline{S_{2n,0}^*}$ of SCH symbol $S_{2n,0}$, and a complex conjugate $C_{2n,1}^*$ of said primary CPICH symbol $C_{2n,1}$;

multipliers calculating $C_{2n,0} \times S_{2n,0}^*$, $C_{2n,0}^* \times S_{2n,0}$ and $C_{2n,1}^* \times C_{2n,1}$; and

an adder calculating a sum of $C_{2n,0} \times S_{2n,0}^* + C_{2n,0}^* \times S_{2n,0} + C_{2n,1}^* \times C_{2n,1}$,

said judgment means makes judgment whether transmission diversity is performed or not depending upon positive or negative of sign of said sum.

3. (original): A transmission diversity detection circuit as set forth in claim 1, wherein said predetermined slot is even numbered slots in one frame, said first and second symbols are (0)th and first symbols of said slot.

4. (original): A transmission diversity detection circuit as set forth in claim 1, wherein said arithmetic means performs arithmetic operation upon performing communication.

5. (original): A transmission diversity detection circuit as set forth in claim 1, wherein said arithmetic means performs arithmetic operation upon registration of position for communication.

6. (currently amended): A transmission diversity detection method for notifying presence or absence of a transmission diversity of spread spectrum communication by modulation of SCH (Synchronization channel), comprising:

calculating a calculated value of $C_{2n,0} \times S_{2n,0}^* + C_{2n,0}^* \times S_{2n,0} + C_{2n,1}^* \times C_{2n,1}$, in first and second symbols in a predetermined number of series of slots with respect to a reception signal, taking a primary CPICH (Common pilot channel) symbol with respect to said first symbol as $C_{2n,0}$, a SCH symbol with respect to said first symbol as $S_{2n,0}$, and a primary CPICH symbol with respect to said second symbol as $C_{2n,1}$, and taking a complex conjugate of said primary CPICH symbol $C_{2n,0}$ as $C_{2n,0}^*$, a complex conjugate of SCH symbol $S_{2n,0}$ as $S_{2n,0}^*$, and a complex conjugate of said primary CPICH symbol $C_{2n,1}$ as $C_{2n,1}^*$; and

judging whether transmission diversity is present or not depending upon positive or negative of said calculated value.

7. (currently amended): A transmission diversity detection method as set forth in claim 6, wherein said calculating step comprises:

deriving said complex conjugate $C_{2n,0}^*$ of said primary CPICH symbol $C_{2n,0}$, a complex conjugate $S_{2n,0}^* S_{2n,0}^*$ of SCH symbol $S_{2n,0}$, and a complex conjugate $C_{2n,1}^*$ of said primary CPICH symbol $C_{2n,1}$;

calculating $C_{2n,0} \times S_{2n,0}^*$, $C_{2n,0}^* \times S_{2n,0}$ and $C_{2n,1}^* \times C_{2n,1}$; and

calculating a sum of $C_{2n,0} \times S_{2n,0}^* + C_{2n,0}^* \times S_{2n,0} + C_{2n,1}^* \times C_{2n,1}$,

said judging step judges whether transmission diversity is performed or not depending upon positive or negative of sign of said sum.

8. (original): A transmission diversity detection method as set forth in claim 6, wherein said predetermined slot is even numbered slots in one frame, said first and second symbols are (0)th and first symbols of said slot.

9. (currently amended): A storage medium storing a program implementing a transmission diversity detection method for notifying presence or absence of a transmission diversity of spread spectrum communication by modulation of SCH (Synchronization channel), said program comprising:

calculating a calculated value of $C_{2n,0} \times S_{2n,0}^* + C_{2n,0}^* \times S_{2n,0} + C_{2n,1}^* \times C_{2n,1}$, in first and second symbols in a predetermined number of series of slots with respect to a reception signal, taking a primary CPICH (Common pilot channel) symbol with respect to said first symbol as $C_{2n,0}$, a SCH symbol with respect to said first symbol as $S_{2n,0}$, and a primary CPICH symbol with respect to said second symbol as $C_{2n,1}$, and taking a complex conjugate of said primary CPICH symbol $C_{2n,0}$ as $C_{2n,0}^*$, a complex conjugate of SCH symbol $S_{2n,0}$ as $S_{2n,0}^*$, and a complex conjugate of said primary CPICH symbol $C_{2n,1}$ as $C_{2n,1}^*$; and

judging whether transmission diversity is present or not depending upon positive or negative of said calculated value.

10. (currently amended): A storage medium as set forth in claim 9, wherein said calculating step comprises:

deriving said complex conjugate $C_{2n,0}^*$ of said primary CPICH symbol $C_{2n,0}$, a complex conjugate $S_{2n,0}^*$ of SCH symbol $S_{2n,0}$, a complex conjugate $C_{2n,1}^*$ of said primary CPICH symbol $C_{2n,1}$ and a complex conjugate $S_{2n,1}^*$ of said SCH symbol $S_{2n,1}$;

calculating $C_{2n,0} \times S_{2n,0}^*$, $C_{2n,0}^* \times S_{2n,0}$ and $C_{2n,1}^* \times C_{2n,1}$; and

calculating a sum of $C_{2n,0} \times S_{2n,0}^* + C_{2n,0}^* \times S_{2n,0} + C_{2n,1}^* \times C_{2n,1}$,

said judging step judges whether transmission diversity is performed or not depending upon positive or negative of sign of said sum.

11. (original): A storage medium as set forth in claim 9, wherein said predetermined slot is even numbered slots in one frame, said first and second symbols are (0)th and first symbols of said slot.